

Data Center Multi-Layer VPC Design Aggregation Layer Failure Scenarios (LACP) Configuration Example: Part I

From DocWiki

Contents

- 1 Introduction
- 2 Topology
- 3 Procedures
- 4 Baseline Configurations for VPC on all routers
- 5 Related Information

Introduction

Test Details: Goals of this test

Data Center Multi-Layer VPC design aggregation layer failure scenarios are depicted in this document. The tests involve a multiple VPC domain design with VPC extended from Core to Aggregation as well as Aggregation to Access. The Failure scenarios covered in this test document are the following:

- Failure of the Peer Keepalive link - simulated by the shutdown of Ethernet1/1 on AGG1 router
- Failure of a single link in the Peer-link bundle - simulated by shutting down either Ethernet2/1 on the AGG1 router
- Failure of the peer-link port-channel - simulated by shutting down the Port-channel 3000 interface between AGG1 and AGG2 routers
- SFM module failure on Aggregation router
- Supervisor failure/switchover on an aggregation router
- Linecard failure on the AGG1 router
- Failure of an aggregation node

Data to Record


Verification of operation of VPC and its configuration using the following commands:

- show vpc brief
- show port-channel summary
- show port-channel traffic
- show run int port-channel xxxx
- show run vpc

Estimated Time: 120 minutes

Topology

Click on thumbnail to enlarge:



Procedures

1. This document highlights the failure scenarios with the above mentioned topology in the Aggregation layer.
2. The following failures were conducted on the Aggregation layer to verify the operation and resiliency of VPC in a multi-domain VPC environment with the entire Data Center running on VPC.

- Failure of the Peer Keepalive link - simulated by the shutdown of Ethernet1/1 on AGG1 router
- Failure of a single link in the Peer-link bundle- Simulated by shutting down either Ethernet2/1 on the AGG1 router
- Failure of the peer-link port-channel- Simulated by shutting down the Port-channel 3000 interface between AGG1 and AGG2 routers
- SFM module failure on Aggregation router
- Supervisor Failure/switchover on an aggregation router
- Linecard failure on the AGG1 router
- Failure of an aggregation node

Baseline Configurations for VPC on all routers

Configs for Core1-VDC1

```
CORE1-F10# show run vpc

!Command: show running-config vpc

version 4.2(1)
feature vpc

vpc domain 1
  peer-keepalive destination 11.21.1.2 source 11.21.1.1 vrf peerkeepalive

interface port-channel150
  vpc 50

interface port-channel1100
  vpc 100

interface port-channel1000
```

```
vpc peer-link
```

```
CORE1-F10# show run int vlan 100
```

```
!Command: show running-config interface Vlan100
```

```
version 4.2(1)
```

```
interface Vlan100
  no shutdown
  description Server Subnet - Vlan 100
  ip address 100.100.11.1/24
  ip router ospf 100 area 0.0.0.0
  hsrp 100
    preempt delay minimum 15
    priority 120
    timers 1 3
    ip 100.100.11.254
```

```
CORE1-F10# show run int port-channel 50
```

```
!Command: show running-config interface port-channel150
```

```
version 4.2(1)
```

```
interface port-channel150
  description Port-Channel to Northbound Test Port (via 6500)
  switchport
  switchport mode trunk
  vpc 50
  switchport trunk allowed vlan 1,100
  spanning-tree port type edge trunk
  spanning-tree bpduguard enable
```

```
CORE1-F10# show run int port-channel 100
```

```
!Command: show running-config interface port-channel1100
```

```
version 4.2(1)
```

```
interface port-channel1100
  description vPC to Aggregation Layer
  switchport
  switchport mode trunk
  vpc 100
  switchport trunk allowed vlan 1,100
```

```
CORE1-F10# show run int port-channel 1000
```

```
!Command: show running-config interface port-channel1000
```

```
version 4.2(1)
```

```
interface port-channel1000
  description vPC Peerlink (eth 2/1,eth 4/1)
  switchport
  switchport mode trunk
  vpc peer-link
  switchport trunk allowed vlan 1,50,100
  spanning-tree port type network
```

```
CORE1-F10# show port-channel summary
```

```
Flags: D - Down      P - Up in port-channel (members)
      I - Individual  H - Hot-standby (LACP only)
      S - Suspended    R - Module-removed
      S - Switched    R - Routed
      U - Up (port-channel)
```

Group	Port-Channel	Type	Protocol	Member Ports
50	Po50 (SU)	Eth	LACP	Eth2/26 (P)
100	Po100 (SU)	Eth	LACP	Eth2/9 (P) Eth2/10 (P)
1000	Po1000 (SU)	Eth	LACP	Eth2/1 (P) Eth4/1 (P)

```
CORE1-F10# show run int eth 2/26

!Command: show running-config interface Ethernet2/26

version 4.2(1)

interface Ethernet2/26
  description Connection to Catalyst 6500 te5/1 (for Connectivity)
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 1,100
  rate-mode dedicated force
  channel-group 50 mode active
  no shutdown

CORE1-F10# show run int eth 2/9

!Command: show running-config interface Ethernet2/9

version 4.2(1)

interface Ethernet2/9
  description Connection to AGG2 eth 2/17
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 1,100
  rate-mode dedicated force
  channel-group 100 mode active
  no shutdown

CORE1-F10# show run int eth 2/10

!Command: show running-config interface Ethernet2/10

version 4.2(1)

interface Ethernet2/10
  description Connection to AGG1 eth 2/17
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 1,100
  rate-mode dedicated force
  channel-group 100 mode active
  no shutdown

CORE1-F10# show run int eth 2/1

!Command: show running-config interface Ethernet2/1

version 4.2(1)

interface Ethernet2/1
  description vPC Peerlink Member Port #1 (por 1000)
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 1,50,100
  rate-mode dedicated force
  udld aggressive
  channel-group 1000 mode active
```

```

no shutdown

CORE1-F10# show run int eth 4/1

!Command: show running-config interface Ethernet4/1

version 4.2(1)

interface Ethernet4/1
  description vPC Peerlink Member Port #2 (por 1000)
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 1,50,100
  rate-mode dedicated force
  udld aggressive
  channel-group 1000 mode active
  no shutdown

CORE1-F10# show vpc brief
Legend:
(*) - local vPC is down, forwarding via vPC peer-link

vPC domain id          : 1
Peer status             : peer adjacency formed ok
vPC keep-alive status   : peer is alive
Configuration consistency status: success
vPC role                : secondary
Number of vPCs configured : 2
Peer Gateway            : Disabled
Dual-active excluded VLANs : -
vPC Peer-link status
-----
id  Port    Status Active vlans
--  --      --      --
1   Po1000 up      1,100

vPC status
-----
id  Port    Status Consistency Reason           Active vlans
--  --      --      --      --
50  Po50    up      success     success       1,100
100 Po100   up      success     success       1,100

```

Configs for Core2-VDC1

```

CORE2-F11# show run vpc

!Command: show running-config vpc

version 4.2(1)
feature vpc

vpc domain 1
  peer-keepalive destination 11.21.1.1 source 11.21.1.2 vrf peerkeepalive

interface port-channel150
  vpc 50

interface port-channel1100
  vpc 100

interface port-channel11000
  vpc peer-link

```

```
CORE2-F11# show run int port-channel 50
!Command: show running-config interface port-channel150

version 4.2(1)

interface port-channel150
description Port-Channel to Northbound Test Port (via 6500)
switchport
switchport mode trunk
vpc 50
switchport trunk allowed vlan 1,100
spanning-tree port type edge trunk
spanning-tree bpdulfiler enable
```

```
CORE2-F11# show run int port-channel 100
!Command: show running-config interface port-channel100

version 4.2(1)

interface port-channel100
description vPC to Aggregation Layer
switchport
switchport mode trunk
switchport trunk allowed vlan 1,100
vpc 100
```

```
CORE2-F11# show run int port-channel 1000
!Command: show running-config interface port-channel1000

version 4.2(1)

interface port-channel1000
description vPC Peerlink (eth 2/1, eth 4/1)
switchport
switchport mode trunk
vpc peer-link
switchport trunk allowed vlan 1,100
spanning-tree port type network
```

```
CORE2-F11# show port-channel summary
Flags: D - Down P - Up in port-channel (members)
      I - Individual H - Hot-standby (LACP only)
      S - Suspended r - Module-removed
      S - Switched R - Routed
      U - Up (port-channel)
```

Group	Port- Channel	Type	Protocol	Member Ports
50	Po50 (SU)	Eth	LACP	Eth2/26 (P)
100	Po100 (SU)	Eth	LACP	Eth2/9 (P) Eth2/10 (P)
1000	Po1000 (SU)	Eth	LACP	Eth2/1 (P) Eth4/1 (P)

```
CORE2-F11# show run int eth 2/26
!Command: show running-config interface Ethernet2/26
```

```
version 4.2(1)

interface Ethernet2/26
description Connection to Catalyst 6500 te5/1 (for Connectivity)
switchport
switchport mode trunk
```

```
switchport trunk allowed vlan 1,100
rate-mode dedicated force
channel-group 50 mode active
no shutdown

CORE2-F11# show run int eth 2/9

!Command: show running-config interface Ethernet2/9

version 4.2(1)

interface Ethernet2/9
description Connection to AGG1 eth 2/18
switchport
switchport mode trunk
switchport trunk allowed vlan 1,100
rate-mode dedicated force
channel-group 100 mode active
no shutdown

CORE2-F11# show run int eth 2/10

!Command: show running-config interface Ethernet2/10

version 4.2(1)

interface Ethernet2/10
description Connection to AGG2 eth 2/18
switchport
switchport mode trunk
switchport trunk allowed vlan 1,100
rate-mode dedicated force
channel-group 100 mode active
no shutdown

CORE2-F11# show run int eth 2/1

!Command: show running-config interface Ethernet2/1

version 4.2(1)

interface Ethernet2/1
description vPC Peerlink Member Port #1 (por 1000)
switchport
switchport mode trunk
switchport trunk allowed vlan 1,100
rate-mode dedicated force
udld aggressive
channel-group 1000 mode active
no shutdown

CORE2-F11# show run int eth 4/1

!Command: show running-config interface Ethernet4/1

version 4.2(1)

interface Ethernet4/1
description vPC Peerlink Member Port #2 (por 1000)
switchport
switchport mode trunk
switchport trunk allowed vlan 1,100
rate-mode dedicated force
udld aggressive
channel-group 1000 mode active
no shutdown
```

```
CORE2-F11# show run int vlan 100
!Command: show running-config interface Vlan100
version 4.2(1)

interface Vlan100
  no shutdown
  description Server Subnet - Vlan 100
  ip address 100.100.11.2/24
  ip router ospf 100 area 0.0.0.0
  hsrp 100
    preempt delay minimum 15
    timers 1 3
    ip 100.100.11.254
```

Configuration of AGG1

```
AGG1-F12# show run vpc
!Command: show running-config vpc

version 4.2(1)
feature vpc

vpc domain 2
  role priority 1
  peer-keepalive destination 111.211.1.2 source 111.211.1.1 vrf peerkeepalive

interface port-channel10
  vpc 10

interface port-channel120
  vpc 20

interface port-channel100
  vpc 100

interface port-channel1200
  vpc 200

interface port-channel1300
  vpc 300

interface port-channel1600
  vpc 600

interface port-channel13000
  vpc peer-link

AGG1-F12# show run int port-channel 10
!Command: show running-config interface port-channel10

version 4.2(1)

interface port-channel10
  description Port Channel to ACC3 Nexus 5K
  switchport
  switchport mode trunk
  vpc 10
  switchport trunk allowed vlan 1,100,200
```

```
AGG1-F12# show run int port-channel 20
```

```
!Command: show running-config interface port-channel20
```

```
version 4.2(1)
```

```
interface port-channel20
  description Port Channel to ACC4 Nexus 5K
  switchport
  switchport mode trunk
  vpc 20
  switchport trunk allowed vlan 1,100,200
```

```
AGG1-F12# show run int port-channel 100
```

```
!Command: show running-config interface port-channel100
```

```
version 4.2(1)
```

```
interface port-channel100
  description Port Channel to Core Layer - VDC1
  switchport
  switchport mode trunk
  vpc 100
  switchport trunk allowed vlan 1,100
```

```
AGG1-F12# show run int port-channel 200
```

```
!Command: show running-config interface port-channel200
```

```
version 4.2(1)
```

```
interface port-channel200
  description Port Channel to Core Layer - VDC2
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 1,200
  vpc 200
```

```
AGG1-F12# show run int port-channel 300
```

```
!Command: show running-config interface port-channel300
```

```
version 4.2(1)
```

```
interface port-channel300
  description Port Channel to Access Layer
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 1,100,200
  vpc 300
```

```
AGG1-F12# show run int port-channel 600
```

```
!Command: show running-config interface port-channel600
```

```
version 4.2(1)
```

```
interface port-channel600
  description Port Channel to SVR-WIN TEAM2 (100.100.11.201)
  switchport
  vpc 600
  switchport access vlan 100
```

```
AGG1-F12# show run int port-channel 3000
```

```
!Command: show running-config interface port-channel3000
```

```
version 4.2(1)
```

```
interface port-channel3000
  description vPC Peerlink
  switchport
  switchport mode trunk
  vpc peer-link
  switchport trunk allowed vlan 1,100,200
  spanning-tree port type network
```

```
AGG1-F12# show port-channel summary
```

```
Flags: D - Down P - Up in port-channel (members)
      I - Individual H - Hot-standby (LACP only)
      S - Suspended r - Module-removed
      S - Switched R - Routed
      U - Up (port-channel)
```

Group	Port- Channel	Type	Protocol	Member Ports
10	Po10 (SU)	Eth	LACP	Eth3/1 (P)
20	Po20 (SU)	Eth	LACP	Eth3/2 (P)
100	Po100 (SU)	Eth	LACP	Eth2/17 (P) Eth2/18 (P)
200	Po200 (SU)	Eth	LACP	Eth2/25 (P) Eth2/26 (P)
300	Po300 (SU)	Eth	LACP	Eth3/9 (P) Eth3/10 (P)
600	Po600 (SU)	Eth	NONE	Eth3/17 (P)
3000	Po3000 (SU)	Eth	LACP	Eth2/1 (P) Eth2/2 (P) Eth3/25 (P) Eth3/26 (P)

```
AGG1-F12# show run int eth 3/1
```

```
!Command: show running-config interface Ethernet3/1
```

```
version 4.2(1)
```

```
interface Ethernet3/1
  description Member Port #1 for Port-Channel 10 (N5K ACC3)
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 1,100,200
  rate-mode dedicated force
  channel-group 10 mode active
  no shutdown
```

```
AGG1-F12# show run int eth 2/1
```

```
!Command: show running-config interface Ethernet2/1
```

```
version 4.2(1)
```

```
interface Ethernet2/1
  description Member port for Peerlink #1
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 1,100,200
  rate-mode dedicated force
  channel-group 3000 mode active
  no shutdown
```

```
AGG1-F12# show vpc brief
```

```
Legend:
```

```
(*) - local vPC is down, forwarding via vPC peer-link
```

```
vPC domain id : 2
Peer status : peer adjacency formed ok
vPC keep-alive status : peer is alive
```

...cisco.com/.../Data_Center_Multi-Layer_VPC_Design_Aggregation_La...

```

Configuration consistency status: success
vPC role : primary
Number of vPCs configured : 6
Peer Gateway : Disabled
Dual-active excluded VLANs : -

vPC Peer-link status
-----
id Port Status Active vlans
-- -- -
1 Po3000 up 1,100,200

vPC status
-----
id Port Status Consistency Reason Active vlans
-- -- -
10 Po10 up success success 1,100,200
20 Po20 up success success 1,100,200
100 Po100 up success success 1,100
200 Po200 up success success 1,200
300 Po300 up success success 1,100,200
600 Po600 up success success 100
-----
```

Configuration of AGG2:

```

AGG2-F13# show run vpc
!Command: show running-config vpc

version 4.2(1)
feature vpc

vpc domain 2
 peer-keepalive destination 111.211.1.1 source 111.211.1.2 vrf peerkeepalive

interface port-channel10
 vpc 10

interface port-channel120
 vpc 20

interface port-channel1100
 vpc 100

interface port-channel1200
 vpc 200

interface port-channel1300
 vpc 300

interface port-channel1600
 vpc 600

interface port-channel13000
 vpc peer-link

AGG2-F13# show run int port-channel 10
!Command: show running-config interface port-channel10

version 4.2(1)

interface port-channel10
 description Port Channel to ACC3 (N5K)
```

```
switchport
switchport mode trunk
vpc 10
switchport trunk allowed vlan 1,100,200

AGG2-F13# show run int port-channel 20
!Command: show running-config interface port-channel120

version 4.2(1)

interface port-channel120
description Port Channel to ACC4 (N5K)
switchport
switchport mode trunk
vpc 20
switchport trunk allowed vlan 1,100,200

AGG2-F13# show run int port-channel 100
!Command: show running-config interface port-channel100

version 4.2(1)

interface port-channel100
description Port Channel to Core Layer VDC1
switchport
switchport mode trunk
vpc 100
switchport trunk allowed vlan 1,100,200

AGG2-F13# show run int port-channel 200
!Command: show running-config interface port-channel1200

version 4.2(1)

interface port-channel1200
description Port Channel to Core Layer VDC2
switchport
switchport mode trunk
vpc 200
switchport trunk allowed vlan 1,100,200

AGG2-F13# show run int port-channel 300
!Command: show running-config interface port-channel1300

version 4.2(1)

interface port-channel1300
description Port Channel to Access Layer N7Ks
switchport
switchport mode trunk
vpc 300
switchport trunk allowed vlan 1,100,200

AGG2-F13# show run int port-channel 600
!Command: show running-config interface port-channel1600

version 4.2(1)

interface port-channel1600
description Port Channel to SVR-WIN TEAM2 (100.100.11.201)
...cisco.com/.../Data_Center_Multi-Layer_VPC_Design_Aggregation_La...
```

```

switchport
vpc 600
switchport access vlan 100

AGG2-F13# show run int port-channel 3000
!Command: show running-config interface port-channel3000

version 4.2(1)

interface port-channel3000
description vPC Peerlink
switchport
switchport mode trunk
switchport trunk allowed vlan 1,100,200
vpc peer-link
spanning-tree port type network

AGG2-F13# show port-channel summary
Flags: D - Down P - Up in port-channel (members)
      I - Individual H - Hot-standby (LACP only)
      s - Suspended r - Module-removed
      S - Switched R - Routed
      U - Up (port-channel)
-----
Group Port-      Type     Protocol Member Ports
      Channel
-----
10    Po10 (SU)   Eth      LACP     Eth3/1(P)
20    Po20 (SU)   Eth      LACP     Eth3/2(P)
100   Po100 (SU)  Eth      LACP     Eth2/17(P)   Eth2/18(P)
200   Po200 (SU)  Eth      LACP     Eth2/25(P)   Eth2/26(P)
300   Po300 (SU)  Eth      LACP     Eth3/9(P)    Eth3/10(P)
600   Po600 (SU)  Eth      NONE    Eth3/17(P)
1000  Po1000 (SD) Eth      NONE    --
3000  Po3000 (SU) Eth      LACP     Eth2/1(P)    Eth2/2(P)    Eth2/9(P)
                                         Eth2/10(P)

AGG2-F13# show run int eth 3/1
!Command: show running-config interface Ethernet3/1

version 4.2(1)

interface Ethernet3/1
description Member Port #1 for Port-Channel 10 (N5K ACC3)
switchport
switchport mode trunk
switchport trunk allowed vlan 1,100,200
rate-mode dedicated force
channel-group 10 mode active
no shutdown

AGG2-F13# show run int eth 2/1
!Command: show running-config interface Ethernet2/1

version 4.2(1)

interface Ethernet2/1
description Peer keep-alive Member Port #1
switchport
switchport mode trunk
switchport trunk allowed vlan 1,100,200
rate-mode dedicated force
channel-group 3000 mode active
no shutdown

```

```

AGG2-F13# show vpc brief
Legend:
(*) - local vPC is down, forwarding via vPC peer-link

vPC domain id : 2
Peer status : peer adjacency formed ok
vPC keep-alive status : peer is alive
Configuration consistency status: success
vPC role : secondary
Number of vPCs configured : 6
Peer Gateway : Disabled
Dual-active excluded VLANs : -

vPC Peer-link status
-----
id Port Status Active vlans
-- -- --
1 Po3000 up 1,100,200

vPC status
-----
id Port Status Consistency Reason Active vlans
-- -- --
10 Po10 up success success 1,100,200
20 Po20 up success success 1,100,200
100 Po100 up success success 1,100
200 Po200 up success success 1,200
300 Po300 up success success 1,100,200
600 Po600 up success success 100

AGG2-F13#
-----
```

Configuration of ACC1:

```

ACC1-I13# show run vpc
!Command: show running-config vpc

version 4.2(1)
feature vpc

vpc domain 1
  role priority 1
  peer-keepalive destination 112.212.1.2 source 112.212.1.1 vrf peerkeepalive

interface port-channel300
  vpc 300

interface port-channel1500
  vpc 500

interface port-channel4000
  vpc peer-link

ACC1-I13# show run int port-channel 300
!Command: show running-config interface port-channel1300

version 4.2(1)

interface port-channel1300
  description Port Channel to AGG Layer N7Ks
  switchport
    switchport mode trunk
```

```

switchport trunk allowed vlan 1,100,200
vpc 300

ACC1-I13# show run int port-channel 500
!Command: show running-config interface port-channel1500

version 4.2(1)

interface port-channel1500
description Port Channel to SVR-WIN (vPC 500)
switchport
vpc 500
switchport access vlan 100

ACC1-I13# show run int port-channel 4000
!Command: show running-config interface port-channel14000

version 4.2(1)

interface port-channel14000
description Peerlink Port Channel (eth2/1 - eth2/2)
switchport
switchport mode trunk
vpc peer-link
switchport trunk allowed vlan 1,100,200
spanning-tree port type network

ACC1-I13# show port-channel summary
Flags: D - Down P - Up in port-channel (members)
      I - Individual H - Hot-standby (LACP only)
      S - Suspended r - Module-removed
      S - Switched R - Routed
      U - Up (port-channel)
-----
Group Port- Type Protocol Member Ports
Channel
-----
300 Po300(SU) Eth LACP Eth2/9(P) Eth2/10(P)
500 Po500(SU) Eth NONE Eth2/17(P)
4000 Po4000(SU) Eth LACP Eth2/1(P) Eth2/2(P)
ACC1-I13# show run int eth 2/9
!Command: show running-config interface Ethernet2/9

version 4.2(1)

interface Ethernet2/9
description Member Port #1 - vPC 300 to AGG Layer
switchport
switchport mode trunk
switchport trunk allowed vlan 1,100,200
rate-mode dedicated force
channel-group 300 mode active
no shutdown

ACC1-I13# show run int eth 2/17
!Command: show running-config interface Ethernet2/17

version 4.2(1)

interface Ethernet2/17
description Connects to SVR-WIN TEAM1 (100.100.11.202)
switchport

```

```

switchport access vlan 100
rate-mode dedicated force
channel-group 500
no shutdown

ACC1-I13# show run int eth 2/1

!Command: show running-config interface Ethernet2/1

version 4.2(1)

interface Ethernet2/1
description Peerlink Member Port #1
switchport
switchport mode trunk
switchport trunk allowed vlan 1,100,200
rate-mode dedicated force
channel-group 4000 mode active
no shutdown

ACC1-I13# show vpc brief
Legend:
(*) - local vPC is down, forwarding via vPC peer-link

vPC domain id : 1
Peer status : peer adjacency formed ok
vPC keep-alive status : peer is alive
Configuration consistency status: success
vPC role : primary
Number of vPCs configured : 2
Peer Gateway : Disabled
Dual-active excluded VLANs : -

vPC Peer-link status
-----
id  Port  Status Active vlans
--  ---  --
1   Po4000 up    1,100,200

vPC status
-----
id  Port  Status Consistency Reason          Active vlans
--  ---  --
300 Po300 up    success      success        1,100,200
500 Po500 up    success      success        100

```

Configuration of ACC2:

```

ACC2-I12# show run vpc

!Command: show running-config vpc

version 4.2(1)
feature vpc

vpc domain 1
peer-keepalive destination 112.212.1.1 source 112.212.1.2 vrf peerkeepalive

interface port-channel1300
vpc 300

interface port-channel1500
vpc 500

```

```

interface port-channel4000
 vpc peer-link

ACC2-I12# show run int port-channel 300
!Command: show running-config interface port-channel300

version 4.2(1)

interface port-channel1300
 description vPC to AGG Layer N7Ks
 switchport
 switchport mode trunk
 vpc 300
 switchport trunk allowed vlan 1,100,200

ACC2-I12# show run int port-channel 500
!Command: show running-config interface port-channel500

version 4.2(1)

interface port-channel1500
 description Port Channel to SVR-WIN TEAM1 (eth 2/17)
 switchport
 vpc 500
 switchport access vlan 100

ACC2-I12# show run int port-channel 4000
!Command: show running-config interface port-channel4000

version 4.2(1)

interface port-channel4000
 description vPC Peerlink (eth 2/1 - eth 2/2)
 switchport
 switchport mode trunk
 vpc peer-link
 switchport trunk allowed vlan 1,100,200
 spanning-tree port type network

ACC2-I12# show port-channel summary
Flags: D - Down P - Up in port-channel (members)
      I - Individual H - Hot-standby (LACP only)
      s - Suspended r - Module-removed
      S - Switched R - Routed
      U - Up (port-channel)
-----
Group Port- Type Protocol Member Ports
      Channel
-----
300 Po300(SU) Eth LACP Eth2/9(P) Eth2/10(P)
500 Po500(SU) Eth NONE Eth2/17(P)
4000 Po4000(SU) Eth LACP Eth2/1(P) Eth2/2(P)
ACC2-I12# show run int eth 2/9
!Command: show running-config interface Ethernet2/9

version 4.2(1)

interface Ethernet2/9
 switchport
 switchport mode trunk
 switchport trunk allowed vlan 1,100,200
 rate-mode dedicated force

```

```

channel-group 300 mode active
no shutdown

ACC2-I12# show run int eth 2/17
!Command: show running-config interface Ethernet2/17

version 4.2(1)

interface Ethernet2/17
switchport
switchport access vlan 100
rate-mode dedicated force
channel-group 500
no shutdown

ACC2-I12# show run int eth 2/1
!Command: show running-config interface Ethernet2/1

version 4.2(1)

interface Ethernet2/1
description Peerlink Member Port #1
switchport
switchport mode trunk
switchport trunk allowed vlan 1,100,200
rate-mode dedicated force
channel-group 4000 mode active
no shutdown

ACC2-I12# show vpc brief
Legend:
(*) - local vPC is down, forwarding via vPC peer-link

vPC domain id : 1
Peer status : peer adjacency formed ok
vPC keep-alive status : peer is alive
Configuration consistency status: success
vPC role : secondary
Number of vPCs configured : 2
Peer Gateway : Disabled
Dual-active excluded VLANs : -

vPC Peer-link status
-----
id  Port  Status Active vlans
--  --  --
1   Po4000 up    1,100,200

vPC status
-----
id  Port  Status Consistency Reason          Active vlans
--  --  --
300 Po300 up    success      success      1,100,200
500 Po500 up    success      success      100

```

Configuration of ACC3:

```

n5k-F10# show port-channel summary
Flags: D - Down      P - Up in port-channel (members)
      I - Individual H - Hot-standby (LACP only)
      S - Suspended   R - Module-removed
      S - Switched   R - Routed

```

U - Up (port-channel)

```

Group Port-      Type      Protocol Member Ports
    Channel

10   Po10(SU)    Eth       LACP      Eth1/1(P)    Eth1/2(P)
n5k-F10# show run int port-channel 10
version 4.0(1a)N2(1a)

interface port-channel10
switchport mode trunk
switchport trunk allowed vlan 1,100,200

n5k-F10# show run int eth 1/1
version 4.0(1a)N2(1a)

interface Ethernet1/1
switchport mode trunk
switchport trunk allowed vlan 1,100,200
channel-group 10 mode active

n5k-F10# show run int eth 1/2
version 4.0(1a)N2(1a)

interface Ethernet1/2
switchport mode trunk
switchport trunk allowed vlan 1,100,200
channel-group 10 mode active

n5k-F10# show run int eth 1/7
version 4.0(1a)N2(1a)

interface Ethernet1/7
spanning-tree port type edge
switchport access vlan 100

```

Configuration of ACC4:

```

n5k-F11# show port-channel summary
Flags: D - Down          P - Up in port-channel (members)
      I - Individual    H - Hot-Standby (LACP only)
      S - Suspended      r - Module-removed
      S - Switched       R - Routed
      U - Up (port-channel)

Group Port-      Type      Protocol Member Ports
    Channel

20   Po20(SU)    Eth       LACP      Eth1/1(P)    Eth1/2(P)
n5k-F11# show run int eth 1/1
version 4.0(1a)N2(1a)

interface Ethernet1/1
switchport mode trunk
switchport trunk allowed vlan 1,100,200
channel-group 20 mode active

n5k-F11# show run int eth 1/2
version 4.0(1a)N2(1a)

interface Ethernet1/2
switchport mode trunk
switchport trunk allowed vlan 1,100,200
channel-group 20 mode active

n5k-F11# show run int port-channel 20
version 4.0(1a)N2(1a)

```

```
interface port-channel120
switchport mode trunk
switchport trunk allowed vlan 1,100,200
```

Related Information

Technical Support & Documentation - Cisco Systems (<http://www.cisco.com/cisco/web/psa/default.html?mode=prod>)

Rating: **0.0/5** (0 votes cast)

Retrieved from "[http://docwiki.cisco.com/wiki/Data_Center_Multi-Layer_VPC_Design_Aggregation_Layer_Failure_Scenarios_\(LACP\)_Configuration_Example:_Part_I](http://docwiki.cisco.com/wiki/Data_Center_Multi-Layer_VPC_Design_Aggregation_Layer_Failure_Scenarios_(LACP)_Configuration_Example:_Part_I)"

Category: Data Center Application Services Configuration Examples

- This page was last modified on 18 November 2011, at 21:38.
- © 1992-2011 Cisco Systems, Inc. All rights reserved. Trademarks